



MATERIAL SAFETY DATA SHEET
#29 SW CLEANER

SECTION I - IDENTIFICATION

TRANSPORTATION EMERGENCY: CHEM-TEL 1-800-255-3924 INFORMATION: 860-347-2505
NFPA PROTECTION X
NFPA HEALTH 3
NFPA FLAMMABILITY 0
NFPA REACTIVITY 1

DU-LITE CORPORATION
171 RIVER ROAD
MIDDLETOWN, CT 06457
PREPARED BY: WALTER J. SMITH
DATE: 1/07/2006

PRODUCT NAME #29 SW CLEANER
DESCRIPTION Soak cleaner for ferrous metals.
DOT DESCRIPT.: CORROSIVE SOLIDS, N.O.S. 8, UN1759, PG-II
(Contains: Sodium Hydroxide, Sodium Carbonate)
DOT LABEL: CORROSIVE DOT PLACARDS: CORROSIVE DIAMOND PLACARD

SECTION II - HAZARDOUS INGREDIENTS

Table with 5 columns: HAZARDOUS COMPONENT, CAS NUMBER, TLV(MG/M3), PEL(MG/M3), PERCENT. Rows include Sodium Hydroxide, Sodium Sulfonate, and Trisodium Phosphate-ANH.

N/E = NOT ESTABLISHED N/A = NOT APPLICABLE

SECTION III - PHYSICAL DATA

BOILING POINT(°F).....N/A SPECIFIC GRAVITY (H2O=1)... 2.28 Est.
VAPOR PRESSURE (mm Hg)....N/A MELTING POINT..... 300°C Est.
VAPOR DENSITY (Air=1)....N/A EVAPORATION RATE..... N/A
SOLUBILITY IN H2O.....Complete PH.....14.0 @ 5%
APPEARANCE/ODOR.....White granular material - No odor.

SECTION IV - REACTIVITY DATA

CHEMICAL STABILITY: Stable CONDITIONS TO AVOID: Heat above 1000°F.
INCOMPATIBLE MATERIALS:
Organic materials, acids, cyanides, aluminum, leather, tin, zinc, food sugars.
DECOMPOSITION PRODUCTS:
Steam, oxides of nitrogen, contact with food sugars may form carbon monoxide,
contact with incompatible metals will release explosive hydrogen gas.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT.....None FLAMMABLE LIMITS.....None
LOWER FLAME LIMIT.....N/A HIGHER FLAME LIMIT.....N/A

IN CASE OF FIRE: Non-flammable. Use water mist to cool fire exposed containers.
SPECIAL FIREFIGHTING PROCEDURES: Do not scatter material with water spray.
Wear protective clothing with self-contained breathing apparatus.
UNUSUAL FIRE HAZARDS: Contact with some metals (i.e. aluminum, tin, zinc, etc.)
may release flammable hydrogen gas. Oxidizer when water is removed.
May increase the flammability of combustibles.
Contact with food sugars may form carbon monoxide.

=====
SECTION VI - HEALTH HAZARD DATA
=====

ROUTES OF ENTRY: Eye contact, skin contact, inhalation, ingestion.
HEALTH HAZARDS (ACUTE, CHRONIC):
Contains STRONG ALKALI (Caustic Soda).
Causes severe eye, skin and tissue burns. May be harmful or fatal if swallowed.
May cause respiratory tract irritation, depending upon exposure.
Avoid contact with eyes, skin or clothing.
CARCINOGENICITY: None. NTP?: No. IARC?: No. OSHA REGULATED?: No.
SYMPTOMS OF EXPOSURE: Eye, skin and respiratory tract irritation.
Eye, skin and tissue burns.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: N/EFIRST AID: INHALATION:
Move victim to fresh air. If not breathing, use artificial respiration.
If breathing is difficult, give oxygen.
Seek medical attention.
EYES: Flush with running water for at least 15 minutes.
Seek medical attention.
SKIN: Wash affected area with plenty of water.
Remove contaminated clothing. Neutralize with vinegar.
Seek medical attention.
INGESTION: If conscious, give plenty of water. Do not induce vomiting.
Seek medical attention.

=====
SECTION VII - PRECAUTIONS/PROCEDURES
=====

IN CASE OF SPILL: Wear proper protective clothing.
Contain spills with inert absorbent. Recover material into a chemical waste container.
Neutralize spill area with dilute acid or water.
WASTE DISPOSAL METHOD: Dilute spent solutions 1:10 with water.
Add Urea and mix well. Slowly add dilute acid till pH is between 7.5-8.5.
Allow sludge to settle. Perform this procedure only in a well ventilated area.
PRECAUTIONS: Wear proper protective clothing when using this product.
Use with adequate ventilation. Wash thoroughly after handling.
Store away from strong acids.
When making a solution, add slowly to room temperature water with constant stirring.
Material gives off intense heat and may erupt if not added slowly and mixed well.
OTHER PRECAUTIONS: Emptied containers of this product may contain hazardous residue.
Clean thoroughly before reusing or discarding.
Do not use a welding torch to cut container.
Do not use for water or food storage.

=====
SECTION VIII - SPECIAL PROTECTION
=====

RESPIRATORY PROTECTION:
Use NIOSH approved respirator if dust or vapors are excessive.
VENTILATION: Normal plant ventilation generally adequate.
MECHANICAL EXHAUST...X
PROTECTIVE GLOVES: Rubber.
LOCAL EXHAUST.....X EYE PROTECTION: Safety goggles, face shield.
OTHER PROTECTIVE EQUIP.. Rubber apron, rubber boots, coveralls.
WORK/HYGIENIC PRACTICES.. Wash thoroughly after handling, launder clothes.

SECTION IX - SARA TITLE III INFORMATION

=====

HAZARDOUS COMPONENT	CERCLA RQ LBS.	SECT 302 TPQ LBS.	SECT 313 TOXIC	SECT 311/312 HAZARDS
SODIUM HYDROXIDE	1000	N/A	NO	A, E
TRISODIUM PHOSPHATE	5000	N/A	NO	A

A=IMMEDIATE (ACUTE HEALTH HAZARD) B=DELAYED (CHRONIC) HEALTH HAZARD
C=FIRE HAZARD D= SUDDEN RELEASE OF PRESSURE HAZARD E=REACTIVE HAZARD

© Du-Lite Corporation 1999. All Rights Reserved.