

*** Section 1 - Chemical Product and Company Identification ***

Product Trade Name: RG-75

Manufacturer Information

Du-Lite Corporation
171 River Road
Middletown, CT 06457

Contact Phone: (860) 347-2505 8:00 AM - 5:00 PM

CHEMTEL Emergency Phone: (800) 255-3924 24 Hours

CHEMTEL international: 01-813-248-0585

Recommended Use: Solvent based rust preventive oil

Restrictions on Use: See Incompatibility, Section 10

*** Section 2 - Hazards Identification ***

OSHA Hazard Communication Standard: Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Not classified as Dangerous Goods for transport purposes.

Hazard Classification: Aspiration Hazard Category 1 | Eye Irritation Category 2A | Flammable Liquid Category 3 | Reproductive Toxicity Category 1B | STOT - SE (Narcosis) Category 3

Labeling:



Signal Word: DANGER!

Hazard Statements: Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child.

PREVENTION: Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges.

FIRST AID/IN CASE OF FIRE: IF SWALLOWED: Immediately call a POISON CENTER/doctor/... IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. In case of fire: Use alcohol resistant foam or normal protein foam for extinction. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor/...if you feel unwell. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

STORAGE: Store in a well-ventilated place. Keep cool. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL: Dispose of contents/container in accordance with all local, regional, national and/or international regulations.

Hazards Not Otherwise Classified: N.A.

Percent of Ingredients of Unknown Toxicity: N.A.

Safety Data Sheet

Product Trade Name: **RG-75**

*** Section 3 - Composition / Information on Ingredients ***

HAZARDOUS INGREDIENT	CAS #	TLV(MG/m3)	PEL(MG/M3)	PERCENT
HYDROCARBON SOLVENT	8032-32-4	100 PPM REC.	N/A	<70
Distillates, Petroleum, Hydrotreated	64742-52-5			15
Mineral Oil	64742-52-5			15
NO HAZARDOUS INGREDIENTS. PRODUCT IS A MIXTURE OF HYDROTHREATED AND/OR ACID TREATED HEAVY NAPHTHENIC DISTILLATES.				

T.S. = Trade Secret

*per CFR 29, Part 1910.1200; ingredients listed only if deemed hazardous and comprise 1% or greater of the composition (0.1% or greater for carcinogens).

Component Related Regulatory Information: This product may be regulated, have exposure limits or other information identified.

*** Section 4 - First Aid Measures ***

If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully.

*** Section 5 - Fire Fighting Measures ***

Flash Point: 127° F (53c)

Upper Flammable Limit N.E.

Flammable Limits: N.E.

Lower Flammable Limit N.E.

Extinguishing Media, PPE and Guidance for FireFighter: Foam. Dry chemical powder. BCF (where regulations permit). Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result. Alert Fire Department and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course.

Fire and Explosion Hazards: Liquid and vapor are flammable. Moderate fire hazard when exposed to heat or Flammables. Vapor forms an explosive mixture with air.

Decomposition Products: Oxides of carbon, aldehydes, various hydrocarbons

*** Section 6 - Accidental Release Measures ***

Containment and Clean up procedures must be conducted in accordance with all local, state, and federal regulations.

Containment and Clean-Up Procedures: Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.

Safety Data Sheet

Product Trade Name: **RG-75**

*** Section 7 - Handling and Storage ***

Handling and Storage Procedures: Containers, even those that have been emptied, may contain explosive vapors. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Contains low boiling substance: Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately. Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Avoid reaction with oxidizing agents. Emptied containers of this product may contain hazardous vapors and residue. Clean thoroughly before reusing or discarding. Do not use a welding torch to cut container. Do not use for water or food storage.

*** Section 8 - Exposure Controls / Personal Protection ***

Exposure Guidelines:

A. General Product Information: Follow all applicable exposure limits. Keep formation of airborne mists to a minimum.

B. Component Exposure Limits:

CAS #	HAZARDOUS INGREDIENT	OSHA PEL(mg/m3)	ACGIH TLV(mg/m3)
8052-31-3	STODDARD SOLVENT	5	5

*OSHA-PEL and ACGIH-TLV are 8-Hour TWA unless otherwise noted.

*per CFR 29, Part 1910.1200; ingredients listed only if deemed hazardous and comprise 1% or greater of the composition (0.1% or greater for carcinogens).

Engineering Controls: Set up ventilation to effectively remove and prevent buildup of any dust, vapor or mist generated from the handling of this product.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face Protective Equipment: Wear appropriate eye protection to prevent eye contact.

Skin Protection: Wear appropriate personal protective clothing to prevent skin contact. The worker should immediately wash the skin when it becomes contaminated. Remove wet or significantly contaminated work clothing and replace.

Respiratory Protection: If ventilation is not sufficient to effectively prevent buildup of dust, mists or vapors, provide appropriate NIOSH/MSHA respiratory protection.

Personal Protective Equipment: Provide eyewash fountains in areas where there is any possibility that workers could be exposed to the substance; this is irrespective of the recommendation involving the wearing of eye protection.

Provide facilities for quickly drenching the body within the immediate work area for emergency use where there is a possibility of exposure. Depending on the specific circumstances, a deluge shower, a sink or hose could be considered adequate.

Safety Data Sheet

Product Trade Name: **RG-75**

*** Section 9 - Physical & Chemical Properties ***

Physical State: Liquid

Color: Amber color, mild petroleum odor.

pH: Not Available

Specific Gravity: 0.79

Evaporation Rate: N.E.

Solubility Water: Insoluble

Vapor Density: N.E.

Vapor Pressure: N.E.

Octanol-Water Coefficient: N.E.

Boiling Point: >300 F

Melting Point: Not Available

Flash Point: 112 F (45)

Auto-Ignition Temperature: N.E.

Decomposition Temperature: N.E.

Flammability Limits - Low: N.E.

Hi: N.E.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability: Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerization will not occur.

Conditions to Avoid: Keep away from heat and sources of ignition

Incompatibility: Strong oxidizers, acids and bases.

Decomposition Products: oxides of carbon, sulfur and various hydrocarbons under thermal decomposition.

Hazardous Polymerization: Will not occur.

*** Section 11 - Toxicological Information ***

Route of Exposure: eye/skin contact, inhalation.

Acute Toxicity:

Safety Data Sheet

Product Trade Name: **RG-75**

A: General Product Information

Eye Contact: There is some evidence to suggest that this material can cause eye irritation and damage in some persons. Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion. The vapor when concentrated has pronounced eye irritation effects and this gives some warning of high vapor concentrations.

Skin Contact: Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Skin Absorption: No information available for this product.

Ingestion: Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Ingestion of soluble barium compounds may result in ulceration of the mucous membranes of the gastrointestinal tract, tightness in the muscles of the face and neck, gastroenteritis, vomiting, diarrhea, muscular tremors and paralysis, anxiety, weakness, labored breathing, cardiac irregularity due to contractions of smooth striated and cardiac muscles (often violent and painful), slow irregular pulse, hypertension, convulsions and respiratory failure. Ingestion of petroleum hydrocarbons can irritate the pharynx, esophagus, stomach and small intestine, and cause swellings and ulcers of the mucous.

Inhalation: Inhalation of vapors or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. Inhalation of vapors may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. There is some evidence to suggest that the material can cause respiratory irritation in some persons.

Chronic Hazards: Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.

Carcinogenicity:

a: Component Carcinogenicity:

None.

NTP: No.
OSHA: No.

IARC: No.

* * * Section 12 - Ecological Information * * *

Ecotoxicity:

A: General Product Information

No information available for this product.

B. Component Analysis - Ecotoxicity - Aquatic Toxicity:

No information available for this product.

Persistence and Mobility: No information available for this product

Environmental: For Propylene Glycol Ethers: log Kow's range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation. Henry's Law Constants are low for all category members, ranging from 5.7×10^{-9} atm-m³/mole for TPM to 2.7×10^{-9} atm-m³/mole for PnB. Environmental Fate: Most are liquids at room temperature and all are water-soluble.

Mobility in Soil: No information available.

Safety Data Sheet

Product Trade Name: **RG-75**

*** Section 13 - Disposal Considerations ***

Wastes must be tested using methods described in 40 CFR Part 261. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous wastes. State and local regulations may differ from Federal disposal regulations. Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.

*** Section 14 - Transportation Information ***

US DOT Information: PETROLEUM PRODUCTS, NOI, NOT D.O.T. REGULATED

Marine Pollutant: No

IMDG Classification: UN1268, PETROLEUM DISTILLATES, N.O.S. (NAPHTHA SOLVENT) (41°C c.c.), 3, PG III

IATA Classification: UN1268, PETROLEUM DISTILLATES, N.O.S. (NAPHTHA SOLVENT) (41°C c.c.), 3, PG III

The data provided in this section is for information only and may not be specific for the package size or mode of transportation. See package label for further details.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

No additional information available.

B: Component Analysis

This material may contain chemicals, requiring identification under SARA Section 302 (40 CFR 355 Appendix A, SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

HAZARDOUS COMPONENT	CERCLA RQ LBS.	SECT 302 TPQ LBS.	SECT 313* TOXIC	SECT 311/312 HAZARDS
LOW AROMATIC HYDROCARBON SOLVENT	N.A.	N.A.	N.A.	A,C

A=IMMEDIATE (ACCUTE HEALTH HAZARD) B=DELAYED (CHRONIC) HEALTH HAZARD C=FIRE HAZARD D=SUDDEN RELEASE OF PRESSURE HAZARD E=REACTIVE HAZARD

Sara 311/312 Hazards:

Immediate (Acute)	TRUE
Chronic*	FALSE
Fire	TRUE
Sudden Release-of-Pressure	FALSE
Reactive	FALSE

State Regulations

A: General Product Information

No additional information available.

Other Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List.

B: Component Analysis - Inventory

*** Section 16 - Other Information ***

Revision Date:

01/02/2023

Safety Data Sheet

Product Trade Name: **RG-75**

Key/Legend:

ACGIH = American Conference of Governmental Industrial Hygienists	NFPA = National Fire Protection Association
CERCLA = Comprehensive Environmental Response, Compensation and Liability Act	NIOSH = National Institute for Occupational Safety and Health
EPA = Environmental Protection Agency	NTP = National Toxicology Program
HMIS = Hazardous Material Identification System	OSHA = Occupational Safety and Health Administration
IARC = International Agency for Research on Cancer	SARA = Superfund Amendments and Reauthorization Act
MSHA = Mine Safety and Health Administration	TSCA = Toxic Substance Control Act

The information presented herein is believed to be factual as it has been derived from the works and opinions of persons believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which Du-Lite Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

This is the end of SDS for RG-75